

165 Mill Lane Mountainside, NJ 07092 908-232-7200

KLINGELHOFER CORPORATION Specializing in the sawing of metals for over 70 years

TECHNICAL DATA

KASTOgripspeed C10

PRECISION CUTTING IN RECORD TIME

- Ergonomic design, total enclosure conforms to industry standards
- 10" color touch screen control for all machine functions
- Automatic setting of all feeds/speeds
- Gripper material feed controlled by ball screw and servomotor
- Automatic trim cut adjustable from 3/8" up to 2"
- Remnant bar ends as short as 3"
- Automatic central lubrication for all slides, ball screws and ways
- Material library for steel grades
- Power driven wire brush to clear the saw blade teeth of chips
- Automatic adjustment of the power driven wire brush, also adjusts automatically to brush wear
- Automatic setting of the saw blade stroke according to the shape and size of the material
- Simple saw blade change—less than three minutes

MACHINE SPECIFICATIONS

SPECIFICATIONS	KASTOgripspeed C10
Round solids, normal and thick-walled tubes	5/2" - 4"
Squares	⁵ /8" - 3 ¹ /8"
Cutting speeds	55-575 feet / minute
Saw blade drive	16.9 HP
Hydraulics	2.4 HP
Bar feed stroke single index	19½"
Shortest remnant length	3"
Working height	371/2"